

VS182A/VS184A

2/4-Port HDMI Splitter

- The VS182A/VS184A HDMI Splitter is the perfect solution for anyone who needs to send one source of digital high definition video to two (VS182A) or four (VS184A) displays at the same time. It supports all HDMI-enabled equipment, such as DVD players, satellite set-top boxes and all HDMI displays.


The VS182A/VS184A HDMI Splitter is HDCP (High Bandwidth Digital Content Protection) compliant, making it effective for use with all HDMI displays in home theater applications, as well as in corporate, educational and commercial settings.

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE



Features

- Connects one HDMI source to two (VS182A), four (VS184A) HDMI displays at the same time
- HDMI (3D, Deep Color, 4kx2k); HDCP Compatible
- Supports resolutions of up to Ultra HD 4kx2k and 1080p Full HD
- Supports Dolby True HD and DTS HD Master Audio
- Long distance transmission – up to 15 m (24 AWG)
- Supports up to 340MHz bandwidth for high performance video
- Signaling rates up to 3.4 Gbits in support of 1080p display
- Plug-and-play – no software installation required



Specifications

Function	VS182A	VS184A
Video Input		
Interface	1 x HDMI Type A Female (Black)	
Impedance	100 Ω	
Max. Distance	1.8 m	
Video Output		
Interface	2 x HDMI Type A Female (Black)	4 x HDMI Type A Female (Black)
Impedance	100 Ω	
Video		
Max. Data Rate	10.2 Gbps (3.4 Gbps Per Lane)	
Max. Pixel Clock	340 MHz	
Compliance	HDMI (3D, Deep Color, 4K); HDCP Compatible	
Max. Resolution	Up to 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)	
Max. Distance	Up to 15 m	
Audio		
Input	1 x HDMI Type A Female (Black)	
Output	2 x HDMI Type A Female (Black)	4 x HDMI Type A Female (Black)
Power		
Connectors	1 x DC Jack	
Consumption	5.3 VDC, 2.0W	5.3 VDC, 4.6W
Environmental		
Operating Temperature	0-50 °C	
Storage Temperature	-20 - 60 °C	
Humidity	0 - 80% RH, Non-Condensing	
Physical Properties		
Housing	Metal	
Weight	0.31 kg	0.47 kg
Dimensions (L x W x H)	12.50 x 8.00 x 2.50 cm	20.00 x 8.00 x 2.50 cm

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Printed 11/2015 V3.0



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.